

RoHS Compliant

A

B

C

D

E




A

B

C

D

E









NOTE:

- 1.MATERIAL SPECIFICATION:
 - 1.HOUSING:HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0.
 - 2.TERMINAL: COPPER ALLOY(C1814)
 - 3.MID PLATE: STAINLESS STEEL(SUS301)
 - 4.FRONT SHELL: STAINLESS STEEL(SUS304)
- 2.PLATING SPECIFICATION:
 - 2-1.TERMINAL:
Ni 50u" MIN. UNDER PLATED OVER ALL.
Au PLATED ON THE FUNCTIONAL AREA OF CONTACT.
(GOLD PLATING THICKNESS FOLLOW THE P/N)
PLATING SPECIFICATIONS OF THE SOLDER AREA FOLLOW THE P/N
 - 2-2.FRONT SHELL:
PLATING SPECIFICATIONS FOLLOW THE P/N
 - 2-3.MID PLATE PLATE:
CLEAR ONLY
- 3.MECHANICAL PERFORMANCE,
 - 3-1.INSERTION FORCE: 0.5~2.0kgf.
 - 3-2.REMOVAL FORCE: 0.8kgf~2.0kgf.
 - 3-3.DURABILITY: 10000 CYCLES.
- 4.ELECTRICAL PERFORMANCE,
 - 4-1. VOLTAGE RATING:5 V DC/AC (RMS. max)
CURRENT RATING:5 AMPS. FOR TOTAL VBUS/GND PINS;
1.25AMPS FOR CC PIN,0.25 AMPS. FOR ALL OTHER CONTACT.
 - 4-2. LLCR:
VBUS & GND PINS AND OTHER PINS: 40mA/PIN MAX.
SHIELD: 50mA/MAX.
LLCR MAX. CHANGE OF ALL PINS: 10mA.
 - 4-3.INSULATION RESISTANCE: 100MΩ MIN
 - 4-4.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.
5. ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -25°C~+85°C.
- 6.IR REFLOW:
THE PEAK TEMPERATURE ON THE BOARD SHALL
BE MAINTAINED FOR 10 SECONDS AT 260°C.

USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBUS2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBUS1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND



RECOMMENDED PCB LAYOUT(TOP VIEW)
THICKNESS 0.80MM;DEFAULT TOLERANCE:±0.05

MEASURE POINT: QUADRANT POINT TANGENCY POINT INTERSECTION POINT	GP TP IP	联晟欣连接器(深圳)有限公司 Lianshengxin Connector (Shenzhen) Co., Ltd											
UNLESS OTHERWISE SPECIFIED,TOLERANCE:		DESIGN	Andy	DATE	2014.12.24	TITLE:	TYPE C 16PIN 母座全贴7.35带双压						
X.	±0.25	CHECKED		DATE		PART NO:	LCK-TCF805M-L735YL-G3	REV:	04	SCALE:	1:1	UNIT:	mm
X.x	±0.20	APPROVED		DATE		DRAWING NO:	102022107SSY	SIZE:	A4	SHEET:	1/1		
X.xx	±0.15												
ANGULAR	±3°												

RoHS Compliant

REEL OFF SECTION
(20 POCKETS Min)


800PCS

PULL OUT DIRECTION
(20 POCKETS Min)

SEE DETAIL X

PEELING DIRECTION
165°~180°
PEELING ANGLE

PULL OUT DIRECTION



LABEL

W+0.5

REEL OFF DIRECTION

W=9.00
0.66

1.50
0.75
Ø0.58

PULL OUT DIRECTION

6.00

DETAIL X

PAPER BOARD

REEL AND TAPE

REEL AND TAPE

PAPER BOARD

FOLDER
PAPER BOARD

CARTON

CONNECTOR (PCS)

REEL

800

CARTON

8000

MEASURE POINT:

QUADRANT POINT

QP

TANGENCY POINT

TP

INTERSECTION POINT

IP

UNLESS OTHERWISE
SPECIFIED, TOLERANCE:

X. ±0.25

X.x ±0.20

X.xx ±0.15

ANGULAR

±3°



联晟欣连接器（深圳）有限公司

Lianshengxin Connector (Shenzhen) Co., Ltd

DESIGN

Andy

DATE

2014.12.24

TITLE:

TYPE C 16PIN 母座全贴7.35带双压

CHECKED

DATE

APPROVED

DATE

PART NO: LCK-TCF805M-L735YL-G3

REV: 04

SCALE: 1:1

UNIT: mm

DRAWING NO: 102022107SSY

SIZE: A4

SHEET: 1/1

UNIT: mm