






RoHS Compliant




BOTTOM VIEW

LONG TYPE	10.40	0.45
SHORT TYPE	9.25	1.60
SPEC	DIM"A"	DIM"B"



USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A2	SSTXp1	B11	SSRXp1
A3	SSTXn1	B10	SSRXn1
A4	Vbus	B9	Vbus
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	Vbus	B4	Vbus
A10	SSRXn2	B3	SSTXn2
A11	SSRXp2	B2	SSTXp2
A12	GND	B1	GND



RECOMMENDED PCB LAYOUT(TOP VIEW)

THICKNESS 0.8.0±0.05MM;DEFAULT TOLERANCE:±0.05

- NOTE:
- MATERIAL SPECIFICATION:
 - HOUSING:HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0.
 - CONTACTS: COPPER ALLOY(C1814)
 - MID PLATE: STAINLESS STEEL(SUS301)
 - FRONT SHELL: STAINLESS STEEL(SUS304)
 - PLATING SPECIFICATION:
 - TERMINAL:

Ni 50u" MIN. UNDER PLATED OVER ALL.

Au PLATED ON THE FUNCTIONAL AREA OF CONTACT.

(GOLD PLATING THICKNESS FOLLOW THE P/N)

PLATING SPECIFICATIONS OF THE SOLDER AREA FOLLOW THE P/N
 - FRONT SHELL:

PLATING SPECIFICATIONS FOLLOW THE P/N
 - MID PLATE:

CLEAR ONLY
 - MECHANICAL PERFORMANCE,
 - INSERTION FORCE: 0.5~2.0kgf.
 - REMOVAL FORCE: 0.8kgf~2.0kgf.
 - DURABILITY: 10000 CYCLES.
 - ELECTRICAL PERFORMANCE,
 - CURRENT RATING:5.0A
VOLTAGE RATING:5.0V
 - LLCR:

VBUS & GND PINS AND OTHER PINS: 40mA/PIN MAX.

SHIELD: 50mA/MAX.

LLCR MAX. CHANGE OF ALL PINS: 10mA.
 - INSULATION RESISTANCE: 100MΩ MIN
 - DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.
 - ENVIRONMENTAL PERFORMANCE:

OPERATING TEMPERATURE: -25°C~+85°C.
 - IR REFLOW:

THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C.

LCK-TCF 909 - LXXX W L- G3

联晟欣
LCK
产品类别
TCF:TYPE C母头
TCM:TYPE C公头
产品流水料号识别码

壳长
L925:9.25
L104:10.4

有柱无柱 T:管装
Y: 有柱
W: 无柱

电镀规格
G1: 1U
G3: 3U
(以此类推)

包装方式
L:圆盘
B:吸塑盒

QUADRANT POINT		QP	 联晟欣连接器（深圳）有限公司 Lianshengxin Connector (Shenzhen) Co., Ltd						
TANGENCY POINT		TP							
INTERSECTION POINT		IP							
UNLESS OTHERWISE SPECIFIED, TOLERANCE:			DESIGN	Andy	DATE	2014.12.24	TITLE:		
X. ±0.25			CHECKED		DATE		USB C F SPLINT CONN		
X.x ±0.20			APPROVED		DATE		WITHOUT EMI PCB=0.8		
X.xx ±0.15			PART NO: LCK-TCF909-LXXXWL-G3				REV: 04	SCALE: 1:1	UNIT: mm
ANGULAR ±3°			DRAWING NO: 102022233				SIZE: A4	SHEET: 1/1	