





RoHS Compliant



CKT	DimA	DimB	DimC
2	1.00	2.50	4.00
3	2.00	3.50	5.00
4	3.00	4.50	6.00
5	4.00	5.50	7.00
6	5.00	6.50	8.00
7	6.00	7.50	9.00
8	7.00	8.50	10.00
9	8.00	9.50	11.00
10	9.00	10.50	12.00
11	10.00	11.50	13.00
12	11.00	12.50	14.00
13	12.00	13.50	15.00
14	13.00	14.50	16.00
15	14.00	15.50	17.00
16	15.00	16.50	18.00
17	16.00	17.50	19.00
18	17.00	18.50	20.00
19	18.00	19.50	21.00
20	19.00	20.50	22.00
22	21.00	22.50	24.00
24	23.00	24.50	26.00
26	25.00	26.50	28.00




序号	项目	描述	备注
1	塑胶	LCP	
2	端子	黄铜	
3	焊片	黄铜	
4	盖子	LCP	



技术指标:

- 塑件表面应光洁、无毛边、无明显收缩、缺陷、裂纹等现象。
- 温度范围: $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ 。
- 额定电压: 50V, AC。
- 接触电阻: $\leq 0.02\Omega$ 。
- 绝缘电阻: $\geq 100\text{M}\Omega$ 。
- 额定电流:

适用电线型号: a. AWG#28: 1.0A (per pin)
b. AWG#30: 1.0A (per pin)
c. AWG#32: 0.8A (per pin)



QUADRANT POINT (QP)
TANGENCY POINT (TP)
INTERSECTION POINT (IP)
UNLESS OTHERWISE SPECIFIED, TOLERANCE:
X. ±0.25
X.x ±0.20
X.xx ±0.15
ANGULAR ±3°

联晟欣连接器(深圳)有限公司
Lianshengxin Connector (Shenzhen) Co., Ltd

DESIGN: Andy DATE: 2014.12.24 TITLE: 1.0Pitch 立贴带扣SMT
CHECKED: DATE: APPROVED: DATE: PART NO: LCK-WF-NH100L-NP REV: 04 SCALE: 1:1 UNIT: mm
DRAWING NO: SIZE: A4 SHEET: 1/1